

Universal Cable & Adapter Kit



A Complete Kit at the Tips of Your Fingers

The universal cable kit contains the tools to properly terminate 3 different length cable sub-assemblies with various connector combinations as specified below. The brass, nickel plated adapters have gold plated center contacts and are housed in their own separate case. They can be easily removed with your fingertips in a work area or out in the field. The adapter kit and cables are then housed in a rugged sealed case.

Electrical Data

Maximum Frequency:	4 GHz
Impedance:	50 Ω nominal
Time Delay:	1.47 ns/ft (4.82 ns/m)
Shielding Effectiveness:	< -90 dB
Dielectric Withstanding Voltage:	10 kV at 60 Hz

Mechanical Data

Jacketed Outer Diameter:	0.275 in (6.99 mm)
Bend Radius:	0.500 in (12.70 mm)
Operating Temp. Range:	-31 to 212° F (-35 to 100° C)
Weight:	0.05 lbs/ft (0.023 kg/m)



Universal Cable Assemblies	Qty
36 in	4
72 in	4
96 in	4

Adapter Kit Contents	Qty
Universal Adapter	6
BNC	2 male, 2 female
F Type	2 male, 2 female
N Type	2 male, 2 female
RCA	2 male, 2 female
SMA	2 male, 2 female
TNC	2 male, 2 female
UHF	2 male, 2 female
Mini-UHF	2 male, 2 female
Double Banana Plug	1
Double Binding Post	1
Signal Sampler	1
Wrench	2

Specifications

Frequency		Attenuation		Conn. Loss dB	VSWR
GHz	Band	db/ft	dB/m		
0.045	UHF	0.03	0.07	0.01	1.10:1
0.512	VHF	0.08	0.27	0.02	1.15:1
1.000	L	0.12	0.39	0.02	1.20:1
2.000	S	0.17	0.57	0.03	1.25:1
3.000		0.22	0.73	0.04	1.30:1
4.000	C	0.26	0.86	0.04	1.35:1

Note: Typical Insertion Loss dB = (Attenuation)(Length) + 2(Conn. Loss)



2098 West Main Street, Stroudsburg, PA 18360

Tel: 1-877-MegaPhase / 570-424-8400

Fax: 1-877-MegaFax / 570-424-6031

www.megaphase.com